

Step modifications of two or more steps to allow for a mobility frame and/or walker access are considered a complex modification. This form should be provided when submitting a complex step modification application using the Home/Access Modifications Application form (D1327) with other supporting documents as outlined in Part K.

As per <u>RAP National Guidelines</u>: DVA does not pay for the installation of steps where steps do not currently exist. DVA does not repair, maintain or replace steps that do not meet the relevant building code and are uneven and /or unsafe.

Modifications are limited to widening/increasing depth of the step tread or reducing the height of the step to accommodate a walking aid such as a walking frame, where simpler access and mobility options are not suitable.

Simpler access options and other options such as a provision of a second walking frame should be considered before submitting a complex step modification application.

In Australia there are no Building Standards that provide recommended dimensions for platform steps to accommodate mobility frame and walker access.

Client Name: D	VA Card No:	:
Date of this specification:		
Has a joint site visit taken place with the building	contractor?	□ Yes □ No
If yes, date of site visit:		
Persons present at site visit:		
Please tick all relevant specificat	ions require	d for this modification.
Occupational Therapist's specifications for major modification – step modifications		Comments
The footprint/dimensions of the client and relevant	☐ Yes	
walking aid	□ No	



Occupational Therapist's specifications for major modification – step modifications		Comments
Location Steps to be installed at the ☐ Front access ☐ Rear access ☐ Internal ☐ External other:		
Landing at door If leading directly to a door, a landing is required at the door	☐ Yes ☐ No ☐ N/A	
Note: Refer to AS 1428.1 (2021) with consideration of circulation space for person, equipment and carer/s.		
Upper landing dimensions comply with AS 1428.1 (2021) - Figures 31 & 32 – Circulation spaces at doorways	☐ Yes ☐ No ☐ N/A	
Doorway clear opening: mm		
Direction of approach to doorway from ramp: ☐ Hinge-side ☐ Latch-side ☐ Front approach		
Top landing to be mm length x mm width		
Platform steps Step tread depth to be mm length x mm width Note: Suggested minimum tread depth 850 mm	☐ Yes ☐ No	
Step height to be mm length x Note: Suggested maximum height 95- 105mm	☐ Yes ☐ No	
The step nosing should have a strip of slip resistant paint /colour contrast, with a minimum slip resistant classification of P3 or R10 (dry surface) or P4 or R11 (wet surface). The width of the strip should be approximately 50-75 mm	☐ Yes ☐ No	
Railing Handrails to be positioned on ☐ Left ☐ Right ☐ Ascending ☐ Bilateral		
Height of handrail(s) mm Has the client been advised of their ongoing responsibilities in terms of maintenance of the platform steps?	☐ Yes ☐ No	





Diagrams with measurements attached (pleas	e attach and tick)	⊔ Yes	⊔ No	
<u>Authority to Install (D1323)</u> attached which reflects the final specifications \square Yes				
OT Signature:	Contact Number:			
OT Name:	Contact Email:			